

```
/******
```

Name : Shubham Satish Tembhurkar

PRN : 1641060

Class : L.Y.B.TECH.

Batch : B1

Sub : CCL

Aim : Write a C program to check whether a string belongs to grammar or not.

```
*****/
```

PROGRAM 1:


```
#include<string.h>
#include<stdio.h> int main() {
int c; char string[20]; int
state=0,count=0;
//printf("\n The string must begin with a and terminate with b"); printf("\n The Given Grammar is:\n");
printf("\tS->aS \n\tS->bR \n\tR->aR \n\tR->bS \n\tR->b\n"); printf("Enter a String To
Be Checked: "); scanf("%s",string);

while(string[count]!='\0')
{
switch(state)
{
case 0: if (string[count]=='a')
state=1;
else state=3;
break;
case 1: if (string[count]=='a')
state=1;
else if(string[count]=='b')
state=2;
else state=3;
break;
case 2: if (string[count]=='b')
state=2;
else state=3; break;
default: break;
}
count++; if(state==3)
break;
} if(state==2)
printf("\nString is
accepted.\n"); else
printf("\nString is not accepted.\n");

return 0;
```

}

OUTPUT :



```
D:\Deepali_LY\CC1\string_checker.exe

The Given Grammar is:
S->aS
S->bR
R->aR
R->bS
R->b
Enter a String To Be Checked: abaa
String is not accepted.
Process returned 0 (0x0)   execution time : 77.832 s
Press any key to continue.
```

PROGRAM 2:

```
#include<stdio.h> #include<string.h> int
```

```
i,j,k,l,m,n=0,o,p,nv,z=0,t,x=0; char
```

```

str[10],temp[20],temp2[20],temp3[20]; struct prod { char
lhs[10],rhs[10][10]; int n; }pro[10]; void findter()
{ for(k=0;k<n;k++)
{ if(temp[i]==pro[k].lhs[0])
{ for(t=0;t<pro[k].n;t++)
{ for(l=0;l<20;l++) temp2[l]='\0';
for(l=i+1;l<strlen(temp);l++) temp2[l-i-1]=temp[l];
for(l=i;l<20;l++) temp[l]='\0';
for(l=0;l<strlen(pro[k].rhs[t]);l++) temp[i+l]=pro[k].rhs[t][l];
strcat(temp,temp2); if(str[i]==temp[i]) return;
else if(str[i]!=temp[i] && temp[i]>=65 && temp[i]<=90) break;
} break; }
} if(temp[i]>=65 &&
temp[i]<=90) findter();
} void main() {
FILE *f;
//clrscr();
for(i=0;i<10;i++)
pro[i].n=0;
f=fopen("grammar.txt","r");
while(!feof(f))
{ fscanf(f,"%s",pro[n].lhs); if(n>0) { if(
strcmp(pro[n].lhs,pro[n-1].lhs) == 0 )
{ pro[n].lhs[0]='\0'; fscanf(f,"%s",pro[n-1].rhs[pro[n-
1].n]);
pro[n-1].n++;
continue;
} } fscanf(f,"%s",pro[n].rhs[pro[n].n]);
pro[n].n++; n++; } printf("\n\nTHE GRAMMAR IS AS
FOLLOWS\n\n"); for(i=0;i<n;i++) for(j=0;j<pro[i].n;j++)
printf("%s -> %s\n",pro[i].lhs,pro[i].rhs[j]); while(1) {
for(l=0;l<10;l++) str[0]=NULL; printf("\n\nENTER ANY STRING ( 0 for
EXIT ) : "); scanf("%s",str); if(str[0]=='0') break;// exit(1);
for(j=0;j<pro[0].n;j++)

```

```

        {           for(l=0;l<20;l++)           temp[l]=NULL;
strcpy(temp,pro[0].rhs[j]);
        m=0;
        for(i=0;i<strlen(str);i++)
        {           if(str[i]==temp[i])
m++;
        else if(str[i]!=temp[i] && temp[i]>=65 && temp[i]<=90)           {
                findter();
                if(str[i]==temp[i])           m++;
        }
        else if( str[i]!=temp[i] && (temp[i]<65 || temp[i]>90) )           break;
        }           if(m==strlen(str) && strlen(str)==strlen(temp))
        {           printf("\n\nTHE STRING can be PARSED !!!");           break;
        }
    }           if(j==pro[0].n)           printf("\n\nTHE STRING can NOT be PARSED
!!!");
    }
}
}

```

OUTPUT:

```

D:\Deepali_VY\CC\String_chk.exe
THE GRAMMAR IS AS FOLLOWS
S -> aaBC
B -> bb
C -> cc
ENTER ANY STRING ( 0 for EXIT ) : aabbcc
THE STRING can be PARSED !!!
ENTER ANY STRING ( 0 for EXIT ) :

```

INPUT FILE: grammar.txt

S aaBC
B bb
C cc

PROGRAM 3:

```
#include<stdio.h>
#include<string.h>

int i,j,k,l,m,np,n=0,o,p,nv,z=0,t,x=0; char
str[10],temp[20],temp2[20],temp3[20];
struct prod { char lhs[10],rhs[10][10];
int n;
}pro[10]; void
findter()
{ for(k=0;k<n;k++)
{ if(temp[i]==pro[k].lhs[0])
{ for(t=0;t<pro[k].n;t++)
{ for(l=0;l<20;l++) temp2[l]='\0';
for(l=i+1;l<strlen(temp);l++) temp2[l-i-1]=temp[l];
for(l=i;l<20;l++) temp[l]='\0';
for(l=0;l<strlen(pro[k].rhs[t]);l++) temp[i+l]=pro[k].rhs[t][l];
strcat(temp,temp2); if(str[i]==temp[i]) return;
else if(str[i]!=temp[i] && temp[i]>=65 && temp[i]<=90)
break;
} break;
} } if(temp[i]>=65 && temp[i]<=90)
findter();
```


```

} int main() {
for(i=0;i<10;i++)
pro[i].n=0;
printf("Enter the Number of Productions: "); scanf("%d",&np);
while(n < np) { scanf("%s",pro[n].lhs); if(n>0) { if(
strcmp(pro[n].lhs,pro[n-1].lhs) == 0 )
{ pro[n].lhs[0]='\0'; scanf("%s",pro[n-1].rhs[pro[n-
1].n]);
pro[n-1].n++;
continue;
} } scanf("%s",pro[n].rhs[pro[n].n]);
pro[n].n++; n++;
}
printf("\n\nTHE GRAMMAR IS AS FOLLOWS\n\n"); for(i=0;i<n;i++)
for(j=0;j<pro[i].n;j++) printf("%s -> %s\n",pro[i].lhs,pro[i].rhs[j]);
while(1) { for(l=0;l<10;l++) str[0]=NULL;
printf("\n\nENTER ANY STRING ( 0 for EXIT ) : "); scanf("%s",str);
if(str[0]=='0') break;// exit(1);
for(j=0;j<pro[0].n;j++)
{ for(l=0;l<20;l++) temp[l]=NULL;
strcpy(temp,pro[0].rhs[j]);
m=0; for(i=0;i<strlen(str);i++)
{ if(str[i]==temp[i])
m++;
else if(str[i]!=temp[i] && temp[i]>=65 && temp[i]<=90) {
findter();
if(str[i]==temp[i]) m++;
}
else if( str[i]!=temp[i] && (temp[i]<65 || temp[i]>90) ) break;
} if(m==strlen(str) && strlen(str)==strlen(temp))
{ printf("\n\nTHE STRING can be PARSED !!!"); break;
} } if(j==pro[0].n) printf("\n\nTHE STRING can NOT be
PARSED !!!");
} return 0;

```

}

OUTPUT :



```
D:\Deepali_LYCC1\cfg_ip.exe
Enter the Number of Productions: 3
S aaBC
B bb
C cc

THE GRAMMAR IS AS FOLLOWS
S -> aaBC
B -> bb
C -> cc

ENTER ANY STRING ( 0 for EXIT ) : aabbcc

THE STRING can be PARSED !!!
ENTER ANY STRING ( 0 for EXIT ) : █
```